

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BLUEPRINT
CERAMICS



ECO FRIENDLY



This collection is designed to challenge the status quo of traditional wooden floors through its daring and unconventional characteristics. The unique nature of the collection lies in its use of porcelain stoneware, masterfully used to mimic the character of aged, personality-rich wood. This results in flooring that doesn't just serve a functional purpose, but tells a story, infusing spaces with an aura of far-off lands and thrilling adventures. These floors, with their potent aesthetic appeal and vibrant originality, do not merely exist in a room - they enhance and define it. This collection, then, goes beyond conventional flooring options to offer floor designs that are not only visually striking but also teeming with personality.

Project Suitability

All project types Internal Walls & Floors
Retail & Hospitality
Residential, Renovation & New Build

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BLUEPRINT
CERAMICS

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BPTG01

9mm 9.5mm
200x200mm 200x1800mm
100x600mm
200x1200mm



BLUEPRINT
CERAMICS

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BPTG02

9mm 9.5mm
200x200mm 200x1800mm
100x600mm
200x1200mm



BLUEPRINT
CERAMICS

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BPTG03

9mm 9.5mm
200x200mm 200x1800mm
100x600mm
200x1200mm



BLUEPRINT
CERAMICS

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BPTG04

9mm	9.5mm
200x200mm	200x1800mm
100x600mm	
200x1200mm	



BLUEPRINT
CERAMICS

TSUGA

WOOD EFFECT PORCELAIN TILES

4 COLOURS | 1 FINISHES | 4 FORMATS



BPTG05

9mm

200x1200mm



BPTG06

BLUEPRINT
CERAMICS

TECHNICAL DATA

FINISHES

SOFT R9

THICKNESS

6/9/9.5mm

TEST DESCRIPTION	TEST REQUIREMENT	VALUE
Length & Width	BS EN ISO 10545-2	Conforms
Thickness	BS EN ISO 10545-2	Conforms
Straightness of Sides	BS EN ISO 10545-2	Conforms
Rectangularity	BS EN ISO 10545-2	Conforms
Flatness	BS EN ISO 10545-2	Conforms
Water Absorbtion	BS EN ISO 10545-3	$\leq 0,1\%$
Flexion Resistance	BS EN ISO 10545-4	9 mm: S ≥ 2.400 N R ≥ 48 N/mm ²
Impact Resistance	BS EN ISO 10545/5	$> 0,80$
Abrasion Resistance	BS EN ISO 10545-6	< 150 mm
Resistance to Thermal Shock	BS EN ISO 10545-12	Conforms
Chemical Resistance	BS EN ISO 10545-13	A/LA/HA
Resistance to Stains	BS EN ISO 10545-14	5

**BLUEPRINT
CERAMICS**